





HSF

NOTES:
 Current Rating: 1.0AMP
 Contact Resistance: 20mΩ Max
 Withstand Voltage: 500V AC/DC
 Insulation Resistance: 1000MΩ Min
 Operation Temperature: -40°C to +105°C

Contact Material: Phosphor Bronze
 Contact plating: Au over Ni
 Insulator Material: PA9T+30%GF UL94V-0

Recommended P.C.B Layout (Top Side)
 (PCB BOARD TOLERANCE ±0.05)



Ordering Information

2385-1 XX S XX CYN T 1

No. of Pins per Row: 02-50 Pin
 Contact Plating: G0=Gold Flash, G3=10μ"Gold, G4=15μ"Gold, G5=30μ"Gold
 Packing: T=Tube

Item	Pitch	Mating
Standard	1.27	1317/1325
Alternate		

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	OPERATION	DRAW	DATE	SCALE	FIT	PART NO.
				X.X ±0.40	JYHuang	2012/07/12	UNIT	mm	2385-1XXSXXCYN1
				X.XX ±0.25	CHECK	DATE	SIZE	A4	TITLE:
A0	2012/07/12	NEW	-----	X.XXX ±0.15	APPROVE	DATE	SHEET	1/1	FH1. 27mm SINGLE ROW 180° DIP H=8.50
				Angle ± 3°			PROJ.	⊕	Customer NO.
				DIM TOL					

WCON
 Http: www.wcon.com
 WCON-Dongguan Tel: +86 769 85358920
 WCON-Kunshan Tel: +86 512 57468408
 Fax: +86 769 85358915
 Fax: +86 512 57468468
 E-mail: sales@wcon.com
 E-mail: salesks@wcon.com